

SPLIT PORTATILE model CF-SPLIT 7.1

PRODUCT FEATURES

Cooling capacity: 6.6 KW

3-speed fan motor

flexible tubing of electrical and water connections

fins adjustable air outlet 45/90 °

30 mt. max distance between indoor and outdoor units

operation range unit: 10-30 ° C

operating range external drive: 10-40 ° C

silent quiet operation

high and low pressure



TECHNICAL DATA

cooling capacity (26 ° C 55% IN, OUT 30 ° C): 6650 W

cooling capacity (26 ° C 55% IN, 30 ° C OUT): 22900 BTU/h

power consumption (26 ° C 55% IN, OUT 30 ° C): 2600 W

current consumption (26 ° C 55% IN, OUT 30 ° C): 12 A

speed:

- Maximum 1500 cm / h
- Media 1400 cm / h
- Low 1150 cm / h

airflow outdoor unit 2100 cm / h

refrigerant R407c - 730 g

high efficiency compressor rotary

sound pressure level: 49 dB (A) at 3m in open field) at average

speed

maximum distance between the 2 units: 30 m

interior Dimensions WxDxH mm: 815x360x1030

external dimensions WxDxH mm: 582x360x460

indoor unit weight 86 Kg

outdoor unit weight 16,5 Kg

power supply: 230/1/50

BENEFIT

The unit is a 6.7kW split unit that can cool specific areas using the three fan speeds using a switch on the front panel of the unit.

The unit has an automatic thermostat, which regulates the air temperature around the set level and is able to operate up to a temperature of 10 ° C.

Installation is fast and easy, literally takes a few minutes.

The hoses are supplied in lengths of 10m (standard included in price). You can also have piping maximum length of 30m.

Full display of warning lights that display quickly anomalies (red light) or proper operation (green light)

APPLICATIONS

places half-open

garage, shops

industries

booths and tents

tents structure in general

mobile structure to be cooled

For more information please feel free to contact CF CHILLER FRIGORIFERI srl



Phone: +39 049 8792774

Fax: +39 049 8797940

Email: info@chiller-frigoriferi.it